SURFACE PREPARATION & FINISHING SOLUTIONS

265 MODEL SHOTBLASTER

Product details:

The 265 Model Shotblaster is a mid range machine, yet powerful and accurate to deliver quick, high quality results. Like all of our shotblasters the body is intelligently designed for stability and to produce a uniform blast pattern. It is easily maneuvered in confined areas and ideal for any project size.

Features:

- Easy change Tuning Kit which can be completed in 15 minutes
- Simple and easy to use with precise controls for operator comfort
- Quick release filter system from side panel entry
- Non wearing magnetic seals for superior sealing and recovery
- Blasting width easily reduced for removal of line markings and weld inspections
- Highly efficient filtration unit for optimum dust control

Applications:

- Removal of coatings, rubber deposits and contaminants from a wide range of background surfaces
- Steel preparation to SA3 standard
- Surface re-texturing including asphalt
- Laitance removal on new concrete





265 SHOTBLASTER MACHINE SPECIFICATION

Dimensions	H 1100mm L 134	0mm W 475r	nm	
Working width	Up to 265mm	Weight	345kg	
Motor	11kw			
Power	415v / 3 phase / 32 amp			
Hand-Arm Vibration Level	2.8m/s ² r.m.s	Usage	up to 7 hours	

2	FII	TFD	COI	I FC	LIUN	LINIT
	ГП	IFR		1 6		111411

Z I ILI LIK COLLECTION ONIT				
Dimensions	H 1620mm	L 1555mm W 720mm		
Weight	350kg	Capacity	160 Litre	
Fan Motor	4kW	Compressor Motor	2.2kW	
Power	415v / 3 phase / 32 amp			

SURFACE PREPARATION & FINISHING SOLUTIONS

265 MODEL SHOTBLASTER

ACCESSORIES



Tuning Kit BLAST-018



Side Liners BLAST-035

Top Liner BLAST265-021



Brush Seals

Side BLAST265-024

Front BLAST265-020



Magnets

Front BLAST265-010

Side BLAST265-009 (2 required)



Skid Seals BLAST265-003



Magnetic Sweeper SWEEPER-001



Steel abrasive / Shot

390 Grade 1.0 – 1.4mm – SHOT0390 460 Grade 1.2 – 1.7mm – SHOT0460 550 Grade 1.4 – 2.0mm – SHOT0550